

U Series Thermal Transfer Overprinter

Suits for 32mm,53mm and 107mm print head
Intermittent & Continuous combined in one



Dual motor ribbon drive technology

Consistent ribbon print gap, optimized ribbon usage

Consistent ribbon tension throughout the entire roll

Easy ribbon loading

Powerful software

UI comes with create and edit function

Option to use PC as an UI

Customizable print function

Modular design

Simple structure, stable performance

Ease in maintenance, minimal servicing

Suits for 32mm,53mm and 107mm print head

Technical References

Model	U32	U53	U107
Print Area	Int.:32x80mm Con.:32 x 180mm	Int.:53x80mm Con.:53x180mm	Int.:107x107mm Con.:107 x 214mm
Print Head	32mm 300DPI	53mm 300DPI	107mm 300DPI
Print Speed	Int.:100mm/s~400mm/s;Con.:Max.800mm/s		Int.:100mm/s~400mm/s Con.:Max.500mm/s
Print Frequency	Max.400 times/minute		Max.300 times/minute
Ribbon Size	33mmx600m	55mmx600m	110mmx600m
	Max 900m,more sizes and colors available		Max 600m,more sizes and colors available
Print Gap	0.5mm and adjustable		
Software Interface	RS232 industrial port/USB transfer/Network Interface		
Hardware Interface	Input:print trigger,encoder		
	Output:Print/Fault		
User Interface	Warning and Error indication Job file creation/Self Diagnostic Industrial PC/Color touch screen with USB ports		
Print Body Features	Multiple Language Input Real date and time/Best before date/Expiry date Image rotation/Font Selection/Logo/Serial numbering Customized Code/Random 2D code/Barcode/Shift code		
Weight	Appr. 6.0KG		Appr.8.0KG
Size	L200mm x H180mm x W160mm		L230mm x H180mm x W245mm
Power/Air Supply	90~240 VAC Max 6 bar compressed air		
Operating Environment	Temperature:0~40 °C Humidity:0~90%		

*Only the length of customized ribbon reaches to Max. 900 M

上海研捷机电设备有限公司
Shanghai Yanjie Technology Co.,Ltd
Shanghai Contact:
Tel:+86-21-62829208
Fax:+86-21-62829209
Email:marketing@yanjietech.com

Overseas Contact:
Tel:+65-82007786
Email:dickson.chan@yanjietech.com



<http://www.yanjietech.com>